

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

In the Specification:

Please cancel page 2 of the specification and substitute as follows:

—BACKGROUND OF THE INVENTION

Field of the Invention

AI
Sub B1

5 The present invention relates to a screening housing for microwave circuits. More particularly, the present invention relates to a screening housing with a plurality of chambers which are screened from one another and which accommodate circuit units.

Description of the Prior Art

Sub B2 10

15 Conventionally, a multi-chamber housing which must accommodate a plurality of microwave circuits screened from one another in a high frequency type manner is produced by milling of the individual chambers from a massive metal body. One of such screening housings is disclosed, for example in the German document DE 35 04 726 C1. The manufacture of such a housing with several high frequency-tight chambers is very expensive.

Another German patent document DE 43 19 965 A1 discloses a housing with separating joints provided, for example between the cover and the housing walls. Sealing profiles are inserted in the separating joints, which are
20 composed of an elastic polymer with embedded metal particles.—

Page 3, lines 8-14, cancel in their entirety and substitute

A2

— In keeping with these and other objects of the invention, a screening housing for microwave circuits according to the present invention comprises a housing body, a cover closing an interior of the housing body, a substrate applied to the inner side of the cover; and means forming a plurality of chambers for accommodating individual circuit units, said means including webs formed on the surface of the substrate facing said housing body so that when said cover closes said housing body said webs form walls separating and screening said chambers from each other. The substrate is made from a polymer embedded with metal particles.—;

Page 3, line ~~17~~, after "substrate" insert —made—;

Page 4, line 3, ~~delete~~ ", in particular polymer with the";
line 4, ~~delete~~ "embedded metal particles".

Page 6, line ~~6~~, cancel "from";
line 7, ~~cancel~~ "outside";
line ~~13~~, change "circuit" to —circuits—.